

# self productos autoadhesivos

SELF, SL - C.I.F. B-08953499  
C/Berguedà esq. Priorat Nave 3 – P. I. Can Casablanças  
08192 Sant Quirze del Vallés - Barcelona – ESPAÑA  
Tel. +34 93 7215253 - Fax. +34 93 7213413  
[self@selfautoadhesivos.com](mailto:self@selfautoadhesivos.com) - [www.selfautoadhesivos.com](http://www.selfautoadhesivos.com)

## 2545

**Product:** Double-sided adhesive mounting tape for permanent bonding of materials such as metal, plastic, wood, paper, glass, ceramic and rubber.

**Product advantages:** High initial adhesion (tack), high shear strength. Excellent resistance to ageing, weathering and UV-radiation. Extensive resistance to the influence of chemicals and solvents (domestic cleansing material and polishing agents).

Due to the high adhesive coating weight the adhesive adapts to surface contours, even on rough surfaces, such as chip board.

**Main application fields:** For making extruded plastic and cover profiles self-adhesive for permanent mounting in the furniture industry.  
Mounting of decorative parts and stay bars.  
Fastening of fascias, holders and cable ducts.  
Mounting of exterior and interior mirrors in plastics housings in automotive industry.

<b>Description:</b> Double sided adhesive tape	<b>Colour:</b> White
<b>Carrier:</b> PVC Film	
<b>Adhesive:</b> Modified Acrylic	
<b>Liner:</b> Siliconized paper	<b>Colour:</b> Havana
<b>Thickness (mm without liner):</b> 0.28	+ - 7 %
<b>Adhesive strength AFERA 4001 (N/25 mm):</b> 14	+ - 3.5
<b>Temperature resistance (°C):</b> -10 +100	

**Storage:** Adhesive tapes have to be stored at room temperature and normal humidity (50-70%)/